



## SCORPIO V

OF A CERTAIN CALIBER .  
THE MOST WELL-KNOWN.

Victrix Scorpio is born to be the ideal firearm for military sniping, with its .338 Lapua Magnum caliber. We've decided to join the most renowned ammunition with an equally reliable rifle

 **VICTRIX**  
A R M A M E N T S

#### Destination use

Law Enforcement  
Military  
Sporting

#### Caliber

.338 Lapua Magnum (1/10)  
.300 Win. Magnum (1/10)  
.300 Norma Magnum (1/10)

#### Barrel length

22"  
26"

#### Weight

6.4 kg (14.11 lb) with an empty magazine, muzzle brake, barrel length 22" and no scope

6.7 kg (14.77 lb) with an empty magazine, muzzle brake, barrel length 26" and no scope

#### Dimension

Closed overall length: 902 mm (35.51")  
Open overall length: 1148 mm (45.20")  
With muzzle brake and barrel length 22"

Closed overall length: 1004 mm (39.53")  
Open overall length: 1250 mm (49.21")  
With muzzle brake and barrel length 26"

#### Base rifle

Lapped match-grade button rifled barrel in AISI 416R  
Barrel muzzle thread M18x1mm  
Buttstock with horizontal and vertical multiple lever adjustments, a retractable monopod with quick positioning adjustment and fine adjustment, and an insulated cheek piece  
Single feed and single stack 7-round magazine  
Reversible EVO button folding system  
Octagonal elliptical forend with M-LOK® system, a 20 MoA integrated monobloc top rail and an integrated monobloc rail for mounting a bipod according to STANAG 4694/Mil std 1913  
Ergonomic and interchangeable zero angle flat top grip for standard AR platform  
20 MoA action rail according to STANAG 4694/Mil std 1913  
Detachable multifunction carry handle with quick mount:
 

- with QM (Quick mount) attachment for picatinny rail
- ergonomic handle
- integrated picatinny rail
- hook for rope attachment
- QD (Quick detach) attachments
- tripod attachment with 1/4" – 20 UNC and 3/8" – 16 UNC threads
- front magnetic bit holder for field maintenance


 Victrix ProAngle detachable muzzle brake featuring 3 forward-canted chambers  
Long action in AISI 630 worked out from billet through milling and turning with finish on electro-discharge and grinding machinery.  
Bolt with three asymmetric lugs: first lug on top of the cylinder in vertical position (at 12 o'clock), two side lugs arranged at an angle of 105 degree lift, dirt/ice grooves integral  
PVD finish on the action and on the bolt  
Victrix Professional Dual-stage trigger, convertible to a single stage trigger, with two positions top safety: standard setting approx. 1000 gr (35.27 oz)  
Explorer Cases case for transport cod. 13513  
User manual and welcome kit

#### Stock colour

Every and each component made of light alloy undergoes a hard black anodising  
CERAKOTE ceramic polymer firearm coatings available in three colours:  
Dark Grey  
Dark Olive Drab Green  
Medium Flat Brown

#### Optional

Side picatinny rails for forend with M-LOK® system according to STANAG 4694/Mil std 1913



VICTRIX  
PROFESSIONAL