

TARGET V

THE FIRST, THE MOST SUCCESSFUL.

Being a forerunner means having a main advantage: time. Our Victrix Target boasts victories in F-Class FTR nationals, worldwide championships, and competitions. Being the first means having a main advantage: time.





Destination use

Sporting by bipod

Caliber

.308 Match (1/11 - 30") .308 Match (1/10 - 32") .308 Match (1/10 - 32") .300 WSM (1/10 - 32") .300 WSM (1/9,5 - 32") .7/270 WSM (1/8,5 - 32") .284 Win. (1/8,5 - 32") .308 Win. (1/11 - 30") 6,5 Creedmoor (1/8,5 - 30") 6,5×47 Lapua (1/8,5 - 30") 6 XC (1/8,5 - 28") 6 BR (1/8,5 - 28")

Barrel length

See section Caliber

Weight

6.34 kg (13.98 lb) no scope, barrel length 28" 6.50 kg (14.33 lb) no scope, barrel length 30" 6.72 kg (14.82 lb) no scope, barrel length 32" The weight may vary of +/- 100 gr (3.53 oz) depending on the origin of the raw material

Dimension

Overall length 1175 mm (46,25") With barrel length 28"

Overall length 1230 mm (48,42") With barrel length 30"

Overall length 1280 mm (50,39") With barrel length 32"

Base rifle

Lapped button rifled barrel in AISI 416R with stainless steel finish, muzzle at 1" $\,$

Laminate wood stock

Anima® system, stock with a monolithic bedding in light alloy 20 MoA action rail in light alloy

Anschutz-type rail in light alloy for mounting a bipod Short Single-shot action in AISI 630 worked out from billet through milling and turning with finish on electro-discharge and grinding machinery. Bolt with three asymmetric lugs: first lug on top of the cylinder in vertical position (at 12 o'clock), two side lugs arranged at an angle of 105 degree lift, dirt/ice grooves integral

PVD finish on the action and on the bolt

Victrix Sporting V Single-stage adjustable trigger: standard setting approx. 60 gr (2.12 oz)

Explorer Cases case for transport cod. 13513

User manual and welcome kit

Stock colour

All stocks are in laminate wood and available in the following colours:
Blue River
Green Mountain

Optional

Vertical Adjustment Victrix Sporting Spacer Victrix Sporting





