



## TORMENTO V

### WITH EXTREME PRECISION.

Victrix Tormento is the rifle chosen by expert shooters to get to extreme distances. Choose among its two calibers, .375 CT and .408 CT. Get even furthest than who believes to get farther.

 **VICTRIX**  
A R M A M E N T S



# TORMENTO V

## DATA SHEET

### Destination use

Law Enforcement  
Military  
Sporting

### Caliber

.375 CT (1/10)  
.408 CT (1/13)

### Barrel length

30"

### Weight

11.5 kg (25.35 lb) with an empty magazine, muzzle brake, fluted barrel length 30" and no scope

### Dimension

Closed overall length: 1201 mm (47.28")

Open overall length: 1447 mm (56.97")

With muzzle brake and fluted barrel length 30"

### Base rifle

Lapped and fluted match-grade button rifled barrel in AISI 416R  
Barrel muzzle thread M24x1mm

Buttstock with horizontal and vertical multiple lever adjustments, a retractable monopod with quick positioning adjustment and fine adjustment, and an insulated cheek piece

Single feed and single stack 7-round magazine

Reversible EVO button folding system

Octagonal elliptical forend with M-LOK® system, a 45 MoA integrated monobloc top rail and an integrated monobloc rail for mounting a bipod according to STANAG 4694/Mil std 1913

Ergonomic and interchangeable zero angle flat top grip for standard AR platform

45 MoA action rail according to STANAG 4694/Mil std 1913

Detachable multifunction carry handle with quick mount:

- with QM (Quick mount) attachment for picatinny rail
- ergonomic handle
- integrated picatinny rail
- hook for rope attachment
- QD (Quick detach) attachments
- tripod attachment with 1/4" – 20 UNC and 3/8" – 16 UNC threads
- front magnetic bit holder for field maintenance

Victrix ProAngle detachable muzzle brake featuring 3 forward-canted chambers

Action in AISI 420 worked out from billet through milling and turning with finish on grinding machinery. Bolt with 3 symmetric lugs: first lug at the bottom of the cylinder in vertical position (at 6 o'clock), two side lugs arranged at an angle of 120 degree, dirt/ice grooves integral

PVD finish on the action and on the bolt

Victrix Professional Plus trigger with two positions top safety: standard setting approx. 1000 gr (35.27 oz)

Explorer Cases case for transport cod. 13513

User manual and welcome kit

### Stock colour

Every and each component made of light alloy undergoes a hard black anodising

CERAKOTE ceramic polymer firearm coatings available in three colours:


Dark Grey

Dark Olive Drab Green

Medium Flat Brown

### Optional

Side picatinny rails for forend with M-LOK® system according to STANAG 4694/Mil std 1913



VICTRIX  
PROFESSIONAL