

VENUS PRO

A NEW ERA

Get ready for a real revolution: our new Victrix Venus PRO is the future of precision shooting! We don't see the future, we build it. And yours is called Victrix Venus PRO, the sporting rifle born not only to compete, but above all to succeed.





Destination use

Sporting ideal for PRS® shooting

Caliber / Twist rate

6 XC (1/8)

6,5 x 47 Lapua (1/7,5)

6,5 x 47 Lapua (1/8.5)

6,5 Creedmoor (1/7,5)

6,5 Creedmoor (1/8.5)

6 Creedmoor (1/8)

.308 Match (1/10)

.308 Match (1/11)

Barrel length

26"

Weight

7 kg (15.43 lb), with an empty magazine, a muzzle thread protector and no scope

Dimension

Closed overall length: 921 mm (36.26") Open overall length: 1160 mm (45.67")

Base rifle

Match-grade button rifled barrel with a stainless steel finish and 1.250 1.000 contour

Barrel muzzle thread M18x1mm

Buttstock with horizontal and vertical multiple button adjustments and an adjustable insulated cheek piece, equipped with a Picatinny rail on the underside

Metal double stack single feed 10-round magazine

Reversible EVO button folding system

High-strength monobloc chassis in light alloy ready to mount accessories or hold ammunition, and an ergonomic thumb rest Light profile forend in light alloy equipped with a side M-LOK® system, an integrated Anschutz-type rail in the middle and an integrated Arca rail that run the entire length

Interchangeable barricade stop to protect the magazine Wider trigger guard

Ergonomic and interchangeable grip for standard AR platform Muzzle thread protector

Short action in AISI 630 worked out from billet with a 20 MoA integrated rail

Bolt with six symmetric lugs, equipped with grooves and an interchangeable bolt lever

PVD finish on the action and on the bolt

Victrix Sporting Plus Single-stage adjustable trigger with a two-position safety: standard setting approx. 400 gr (14.11 oz) Explorer Cases case for transport cod. 13513

User manual and welcome kit

Stock colour

Finish: hard black anodised

CERAKOTE ceramic polymer firearm coating available in:

Hit Blue

Every and each component made of light alloy undergoes a hard black anodising.

Optional

Handguard cover on the front with a 20 MoA Picatinny rail 172,5 mm (6.79")

Handguard cover on the front with a 20 MoA Picatinny rail 296 mm (11.65")

Side forend weights for M-LOK® system





